

# MyAQUA Perfect Taste

## Filter solution for your tap water

- Reliable appliance protection for household appliances such as coffee machines and kettles: The filter reduces the limescale content of the water.
- Best taste for hot and cold beverages thanks to magnesium.
- Perfectly filtered drinking water directly from the kitchen tap for your daily use.
- Reliable limescale protection for your kitchen appliances.
- The filter reduces the chlorine content in the water. Therefore the water tastes better.
- The filter reduces heavy metals.
- Suitable for original BWT MyAQUA and BWT AQAdrink filter heads

## The multiple water filtration process

- 1. Primary filtration** - filters particles, e. g. sand or rust.
- 2. Ion exchanger** - reduces water hardness and heavy metals and releases the valuable mineral magnesium into the water.
- 3. Activated-carbon filtration** - reduces substances impairing taste and smell, such as chlorine and organic impurities.



**Perfect filtration**



**Chlorine reduction**




**Limescale protection**



**Perfect taste**

## Technical Data MyAQUA Perfect Taste

Article Number		125558004-C	
Filter Capacity <sup>1</sup>	l	650	
<b>Equipment</b>			
MyAQUA Filter Head <sup>2</sup>		Ø 3/8" x 3/8" (male thread)	
<b>Operating Conditions</b>			
Working Pressure Range	bar	2–7	
Intake Water Pressure	bar	>1,2	
Water Temperature (min. - max.)	°C	+4 to +30	
Ambient Temperature (min. - max.)	°C	+4 to +40	
Ambient Temperature Storage/Transportation (min. - max.)	°C	-20 to +40	
Nominal Flow	l/h	180	
Operating Position		vertical/horizontal	
<b>Dimension &amp; Weights</b>			
	Height with wall mounting bracket	mm	420
	Height without wall mounting bracket	mm	385
Height to Center to Connection	mm		341
Ø Filter Cartridge	mm		89
approx. Filter Cartridge Weight	kg		0,9

<sup>1</sup> The indicated filter capacity is valid for standardised lab conditions. In operation the capacity can vary due to different parameters. Replace the filter cartridge when capacity is exhausted, the flow rate noticeably decreases and at least every 6 months. 15-17° dGH (German total hardness)

<sup>2</sup> With backflow preventer and Aquastop for a simple filter change without water discharge.