

MyAQUA Protect

Filter solution for your tap water

- Perfectly filtered drinking water directly from the kitchen tap for your daily use.
- Provides reliable limescale protection.
- The filter reduces the chlorine content in the water. Therefore the water tastes better.
- The filter reduces heavy metals.
- Suitable for original BWT MyAQUA and BWT AQAdrink filter heads.

The multiple water filtration process

- 1. Primary filtration filters particles, e. g. sand or rust.
- 2. **Ion exchanger -** provides reliable limescale protection and reduces heavy metals.
- **3. Activated-carbon filtration -** reduces substances impairing taste and smell, such as chlorine and organic impurities.









Technichal Data MyAQUA Protect

Article Number		125558003-C
Filter Capacity ¹	I	650
Equipment		
MyAQUA Filter Head²		\emptyset ³ /8" x ³ /8" (male thread)
Operating Conditions		
Working Pressure Range	bar	2–7
Inlet Water Pressure	bar	>1,2
Water Temperature (min max.)	°C	+4 to +30
Ambient Temperature (min max.)	°C	+4 to +40
Ambient Temperature Storage/Transportation (min max.)	°C	-20 to +40
Nominal Flow	l/h	180
Operating Position		vertical/horizontal
Dimension & Weights		
Height with wall mounting bracket Height without wall mounting bracket	mm mm	420 385
Height to Center to Connection	mm	341
Ø Filter Cartridge	mm	89
approx. Filter Cartridge Weight	kg	0,9

¹ The indicated filter capacity is valid for standardised lab conditions. In operation the capacity can vary due to different parameters. Replace the filter cartridge when capacity is exhausted the flow rate nationably degrees and at least every 6 months. 15, 176 (IVI) (Common carbonate hardness)

BWT Holding GmbH

exhausted, the flow rate noticeably decreases and at least every 6 months. 15-17° gKH (German carbonate hardness)

With backflow preventer and Aquastop for a simple filter change without water discharge.