

BWT bestprotect




The protectors

WATER WITH THE PROTECTION FACTOR FOR CATERING AND VENDING

With BWT bestprotect, you can optimise raw water for catering application in a targeted way. This filter system ensures balanced mineralisation and a consistently high pH value in the filtrate – key factors that minimise the risk of corrosion. Hardness-forming calcium ions are practically entirely removed and deposits of limescale and gypsum prevented in the case of raw water containing carbonates or sulphates. Insoluble or difficult-to-remove deposits in machines are now a thing of the past.

The filter system consists of a filter cartridge with a BWT besthead filter head (see graphic). Check valves in the filter head prevent water backflow and uncontrolled water discharge. BWT bestprotect food-safe filter systems are pressure-resistant and safe. They can be used worldwide in any drinking water system.



BWT bestprotect

TECHNICAL DATA

Size	S	V	XL	2XL
Height without handle (A) in mm	360	420	500	574
Height with handle (B) in mm	385	445	530	600
Connection height (C) in mm	310	370	450	520
Ø filter cartridge (D) in mm	88	115	145	185
Weight in kg (dry/wet)	0.9/1.5	2.1/3.2	3.8/6.0	7.5/11.0
Order no. for filter cartridge	FS22N00A00	FS23N00A00	FS28N00A00	FS30N00A00

SETTINGS AND CAPACITIES⁽¹⁾ (no blend setting)


Hot beverage preparation with steam generation / Combination steamer/oven				
Total hardness ⁽²⁾	Size			
	S	V	XL	2XL
≤ 7 °TH	≥ 855	≥ 2140	≥ 5125	≥ 8570
8 °TH	750	1875	4458	7500
10 °TH	600	1500	3590	6000
12 °TH	505	1250	2620	5000
14 °TH	440	1070	2245	4285
17 °TH	380	880	1850	3525
20 °TH	310	750	1570	3000
23 °TH	240	600	1175	2400
≥ 25 °TH	≤ 225	≤ 556	≤ 1090	≤ 2220

⁽¹⁾ Capacities may deviate by up to ±5 % depending on the local water quality and volume flow.

⁽²⁾ °TH = Total hardness. Subject to change.

ACCESSORIES

	Connection	Order number
BWT besthead FLEX filter head	BWT besthead FLEX with 2 connectors 90° elbow, FLEX Insert, M 3/8" made from GFP	FS00Z20A00
BWT besthead FLEX Set 1	BWT besthead FLEX with 2 connectors 90° elbow, FLEX Insert, M 3/8" made from GFP, Connection hose DN 8, 1.5 m, with ball valve, FLEX Insert 90° elbow made from GFP, cap nut FM 3/8", Connector straight, FLEX Insert × M 3/8" made from GFP, Reduction FM 3/4" × M 3/8" made from GFP	FS00Z39A00



MANUFACTURER:

BWT water + more GmbH
Walter-Simmer-Str. 4
A-5310 Mondsee

@waterforcoffeelovers

www.bwt.dk/horeca

SALES:

BWT Denmark: salg@bwt.dk · Tel.: +45 43 600 500

BWT Sweden: info@bwtwater.se · Tel.: +46 40691 4500

BWT Norway: firmapost@bwtwater.no · Tel.: +47 6717 7000

BWT Finland: info@bwtwater.fi · Tel.: +358 (0)2-436 7300

BWT
BEST WATER TECHNOLOGY